

RD19 Rugged Display



An advanced display for advanced communications

Get the most out of your communications setup with the RD19 display. It's rugged enough to perform wherever you need it and its customizable mounting options let you create the most convenient solution. And with features like remote on/off control and an optional touch screen interface, the RD19 is a smart way to enhance a modern control centre.

Guaranteed performance

Our products always come with lifetime support to ensure your equipment maintains peak performance for many missions to come.



Benefits

- Invisible mode (Wire)
- Remote on/off key (via DP-DVI)
- Heater
- IP54

RD19 Rugged Display

Technical Specification

Display	19" TFT Colour display
Resolution	SXGA 1280 x 1024
Colour	16.7 million colours
Viewing angle	Vertical: 80° Horizontal: 80°
Contrast	1000:1
Luminance	350 cd/m ²
Reaction time	5 ms
Interfaces	1 x DP-DVI 1 x VGA 1 x USB 1 x DC-in
Power Consumption	Max 30W (85 with heater)
Options	Remote function, Invisible mode, Heater(-25 °C operating), touchscreen, carrying handles
Dimensions	480 x 405 x 77,5
Weight	10.7 kg
Case	Steel and aluminium
Certification	CE, IP54, VG96916 T5, MIL-STD-810F and MIL-STD 461F (Ground Army)*

Designed to meet:

MIL-STD-810F	Operating	Storage
Altitude Method 500.4, (procedure II, I II)	4572 m (15000 ft)	4572 m (15000 ft)
Shock Method 516.5, (procedure I)	15 G, 3 ms	25 G, 6 ms
Temperature Method 501.4 & Method 502.4, (procedure I, II)	-25 °C to 55 °C	-25 °C to 60 °C
Vibration Method 514.5, (category 2 & 20b)	5-500 Hz, 1G	5-500 Hz, 2 G

*Designed to meet

